

## Flow Switches

Instrument Model	Sensor and Material	Range	Line Size	Max. Working Pressure	Contact Current Rating	Enclosure
<b>AM</b> (Air Ducts)	<b>Paddle</b> 316 SS	Velocity 2 – 5 to 3.5 – 9 M/Sec.	—	0.2 bar	15A 250V AC	Weatherproof
<b>BM</b> (1 × SPCO)	<b>Paddle</b> 316 SS	3 – 9 to 2000 – 3080 LPM	15 to 300 mm	15 / 30 bar	15A 250V AC	Weatherproof
<b>BGM</b> (2 × SPCO)	<b>Paddle</b> 316 SS	3 – 9 to 2000 – 3080 LPM	15 to 300 mm	15 / 30 bar	15A 250V AC	Weatherproof
<b>GK–BM</b> (2 × SPCO)	<b>Paddle</b> 316 SS	3 – 9 to 2000 – 3080 LPM	15 to 300 mm	15 / 30 bar	15A 250V AC	Weatherproof / Flameproof
<b>CM</b> (OEM Series)	<b>Paddle</b> 316 SS	3 – 9 to 2000 – 4000 LPM	15 to 300 mm	10 bar	15A 250V AC	Weatherproof
<b>SM</b> (Fire Fighting Alarm)	<b>Paddle</b> HDPE	15 to 40 LPM	50 to 150 mm	15 bar	15A 250V AC	Weatherproof
<b>FM</b> (Low Flow)	<b>Piston</b> Brass	0.4 to 23 LPM	8 to 15 mm	20 / 100 bar	5A 250V AC	Weatherproof / Flameproof
<b>HR</b> (Hydraulic Systems & SPM's)	<b>316 SS Piston</b> with Magnet	0.5 – 5 to 330 – 500 LPM	8 to 80 mm	50 / 100 bar	80 VA (0.35A 220V AC) 25W	Weatherproof
<b>HRM</b> (HR with 65 mm Gauge)	<b>316 SS Piston</b> with Magnet	0.5 – 5 to 330 – 500 LPM	8 to 80 mm	50 / 100 bar	80 VA (0.35A 220V AC) 25W	Weatherproof
<b>PM</b> (OEM Series)	<b>Paddle</b> 316 SS	2 – 3.5 to 60 – 70 LPM	10 to 50 mm	16 bar	5A 250V AC	Weatherproof
<b>UZ</b> (Water Flow Meter with Switching)	<b>Paddle</b> 316 SS	4 – 40 to 50 – 500 LPM	15 to 50 mm	16 bar	5A 250V AC	Weatherproof
<b>HM</b> (All Plastic) For Corrosive Application (SS Version optional)	<b>Paddle</b> ABS	4 – 4.5 to 65 – 75 LPM	25 to 150 mm	15 bar (100 bar for SS Version)	15A 250V AC	Weatherproof